
S-4232D

Direct Thermal Label Printer



- 203 dpi resolution
 - Fast print speed up to 8 inch/s
 - Support media width from 40mm to 120mm
 - Support Thermal paper, Thermal label, Adhesive thermal paper etc.
-

S-4232D

Specifications

Print Method	Direct Thermal
Print Resolution	203 dpi
Print Speed	2~8 inch/s (51-203mm/s)
Print Width	Max. 104mm (4.09")
Print Length	Max. 2286mm (90")
Dot Density	203dots/inch (8dots/mm)
Dot Size	0.125x0.125mm (1mm=8dots)
Print Head	50KM
Interface	USB
Memory	4M flash, 8M sdram
Media Sensor	Reflective and Transmissive Sensors (adjustable)
Command set	TSPL emulation

Media Characteristics

Media Roll OD	130mm (5")
Media Type	Continuous, black mark, gap, punched hole, Fan fold and more labels
Media Rolling Up Method	Printing side outward rolling
Media Width	Max.120mm (4.72") Min.40mm (1.56")
Media Thickness	Max. 0.254mm (10mil) Min. 0.06mm (2.36mil)
Media Roll Core Size	25.4mm~38mm (1"~1.5")
Media Gap	Min. 2 mm (0.09")
Label Length	10~2286mm (0 39"~90")

[Notice] : Specification are subject to change without notice

S-4232D

BarCode/Fonts/Graphics Symbologie

Enlargement&Rotation	1 ~10 times enlargement in both directions; 0°,90°,270°,360°rotation
Character Size	Font 0 ~ font 8
1D Barcode	Code39, Code93, Code128 subsets A,B,C,Codabar,Interleaved 2 of 5, EAN-13, EAN-14, EAN-128,UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, china POS, ITF1
2D Barcode	QR code
Graphics Processing	Support BMP/PCX/BAS files

Operating Characteristics

Power supply	Input: AC 110V/240V Output: DC24V/2.5A, 60W
Operation Condition	Temperature: 5~45°C(41~104°F), Humidity: 25~85%RH
สภาพการจัดเก็บ	Temperature: -10~50°C(-10~140°F), Humidity: 10%~90%RH

Physical Characteristics

Printer Dimensions	285*210*180mm (WxDxH)
Printer Weight	Approx. 2.1KG

[Notice] : Specification are subject to change without notice

