

IDA-11C1

1D USB Cable scanner

Performance Parameter

Light Source	650mm Visible red light diode	
Scanning Distance	0~280mm @UPC/EAN 0.33mil PCS=90%	
Scan Line	Single line	
Scan Speed	100 scan/sec	
Barcode Sensitivity :	Pitch	±65°
	Roll	±30°
	Skew	±55°
Barcode Type :	1D : UPC/EAN/JAN,UPC-A&UPC-E,EAN-8&EAN-3,JAN-8&JAN-13, ISBN/ISSN, Code39(with full ASCII),Codabar(NW7),Code128&EAN128, Code93, Interleaved 2 of 5 (TTF),Addendum 2 of 5,IATA Code,MSI/Plessy, China Postal Code,Code32(Italian Pharmacode),RSS 14,RSS Limited, RSS Expanded	

Mechanical and Electric Performance

Size(LengthxWidthxHeight)	160mm*67mm*94mm
Weight (without cable)	173g
Indicator	Beeper and Led light
Input voltage	5VDC±10%
Working Current	85mA
Communication Interface	HID USB, USB Virtual COM, RS-232

Environmental Parameter

Storage Temperature	-40°C ~ 60°C
Working Temperature	0°C ~ 50°C
Relative Humidity	5% ~ 95%
Drop Resistance	1.5M
IP Rating	IP52
EMC	CE EN55022 B, VCCI, BSMI
Laser Safety	CDRH Class IIa, IEC 60825-1 Class 1



Certificates

CE,RoHS,EMC,LVD, ISO9001:2008, ISO14001:2004