

# **R550** Extremely Durable Resin

## **Ribbon Properties**

Description	Result	Test Method
Ink	Resin	
Color	Black	Visual
Total Thickness	$6.5 \pm 0.9 \mu$	Weight
Base Film Thickness	$4.5 \pm 0.4 \mu$	Weight

## **Durability of Printed Image**

Label Stock: Top-Coated Polyester

Print Speed: 4 IPS

Description	Result	Test Method
Print Density	> 2.07	Densitometer
Smudge Resistance	A*	Colorfastness Tester - 400 Cycles 500 Grams with Cotton Cloth
Scratch Resistance	A*	Colorfastness Tester - 50 Cycles 200 Grams with Stainless Steel Pointed Tip

<sup>\*</sup>American National Standard Institute (ANSI) Grade Levels A, B, C, D, and F, where A is excellent, B is above average, C is average, D is below average, and F is poor.

#### **Conversion Chart**

Millimatora (mm) to Inches - mm + 25 4	In the Carlotte Control of the Control
Millimeters (mm) to Inches = mm ÷ 25.4	Inches to Millimeters (mm) = Inches ÷ 0.03937
Meters (m) to Feet (ft) = $m \div 0.3048$	Feet (ft) to Meters (m) = Feet ÷ 3.2808
$C^{\circ}$ to $F^{\circ}$ = (1.8 X $C^{\circ}$ ) + 32 = $F^{\circ}$	$F^{\circ}$ to $C^{\circ} = (F^{\circ} \div 1.8) - 17.77$
Thousand square inches (MSI) to $m^2$ = MSI X 0.645	$MSI = m^2 \div 0.645$







The information on this data sheet was obtained in DNP laboratories. Measured values may vary slightly when tested in a different environment. Information contained within this document is subject to change without notification.

DNP Imagingcomm Asia Sdn. Bhd. PLO 676 Jalan Nikel 4
Kawasan Perindustrian Pasir Gudang 81700 Pasir Gudang, Johor Malaysia Office DID: +607.257.8440
Email: ttrsales@dnp.imgcomm.asia

# Technical Data Sheet

# **Extremely Durable Resin**

## **Product Description**

R550 is designed for extreme resistance against most chemicals used in the automotive, chemical, pharma, electronics and other industries. Enjoy the benefit of printing extremely small, crisp and clearly readable characters with great precision. Next to its extreme durability, R550 offers a smooth ink transfer at lower heat settings, which makes R550 compatible to a broad range of durable substrates.

## **Recommended Applications**



Automotive



Chemical



**Electronics** 



Health & Beauty



**Inventory & Logistics** 



Outdoor



Pharmaceutical

#### **Recommended Substrates**

Economy Synthetics Polyesters, Polypropylene, Polyethylene

Specialty Materials

Polyimide **PVC** cards PET cards Vinyls

### **Performance Characteristics**

- Unique high abrasion and solvent resistance
- Excellent readability of small characters
- High density printing ensuring edge definition
- Easy to use at medium printer heat settings
- Anti-static for easy handling and extended printhead life
- DNP's specially formulated backcoating for printhead protection



DNP Imagingcomm Asia Sdn. Bhd. PLO 676 Jalan Nikel 4 Kawasan Perindustrian Pasir Gudang 81700 Pasir Gudang, Johor Malaysia Office DID: +607.257.8440 Email: ttrsales@dnp.imgcomm.asia