

TDD-OFTM-BF238

23.8" Bezel-free Open Frame PCAP Touch Monitors



Overview

The TDD open frame touch monitors include bezel-free & flat bezel types with PCAP or resistive touch technology, which delivers an industrial & reliable solution with outstanding image clarity and accurate touch response that is cost-effective for OEMs and systems integrators. Embedded eye-catching and rugged bezel with flush front finish structure delivers flat design with high durability and scratch & water resistance. It is available in a wide range of sizes (7" to 55"), offering the versatility for embedded kiosk applications from self-service, gaming, industrial automation to digital signage & healthcare.

Features

- Touch thru glass enabled with PCAP supports thickness up to 5mm
- Embedded design with sturdy metal or aluminum (optional for back) enclosure
- IP65 (front) for water and dust protection; Flexible mounting in any table, kiosk, or cabinet design

Specifications

Panel

Diagonal Size	23.8"(16:9), 60.5cm, Active matrix TFT LCD (LED)
Active Area (mm)	527.04 mm x 296.46 mm
Resolution	1920 x 1080
Viewing Angle	Horizontal: 89° or 178° total / Vertical: 89° or 178° total
Number of Colors	16.7 million
Brightness (typical)	Panel: 250 nits / With PCAP Touch: 215 nits
Response Time-total	16 msec typical
Contrast Ratio	3000:1
Input Video Frequency	Horizontal: 30 - 60 KHz / Vertical: 50 - 75 Hz

Touch

Touch Technology	PCAP (Projected Capacitive) - 10 Touch Capacity
Surface Treatment	Water, Dust & Vandal proof, Anti-glare; Anti-fingerprint, Anti-smudge, Anti-bacterial (optional)
Supported OS	Windows / Android / Linux / Mac

Interfaces / Connectors / Controls

Video Interfaces	VGA x1 / HDMI x1 / DVI x1 / Display Port x1 (optional)/ USB x1 for Touch; HDCP: Yes
Connectors & Controls	Audio Mini jack x1 / DC x1; 5 OSD buttons

Power	Supply / Consumption: 100-240 VAC / 12VDC +/- 5%; 25W typical, 1.5W sleep, 0.5W off
Mechanical	Sizes & Weight / Mount: 575.6mm x 349.8mm x 41.2mm / 7.95 kg unpackageg; 75 / 100mm

Environmental	Operating Temperature: 0°C to 50°C
----------------------	------------------------------------

Accessories	Power adapter / cable, HDMI / VGA / Touch USB cable, Flush Mount Brackets w/Screws
--------------------	--

Others	MTBF / Warranty / Enclosure Color: 50,000 hours demonstrated / 1-year / black
---------------	---