

---

# TP-3260VL

Thermal Receipt Printer



- ESC/POS command sets compatible
  - Interface: serial +USB+100M Ethernet standard
  - Support Network Auto-reconnection after disconnect
  - Support black mark media printing
  - Built-in Web IP tools
  - Support 2D barcode printing – QR code
  - Support Windows 32/64bits / Linux / OPOS
-

# TP-3260VL

## Specification

Print Method	Direct thermal line
Print Width	64mm or 72mm
Printing Speed	260mm/second
Auto Cutter	Full or Partial Cut
Dot Density	512dot/line or 576dot/line
Paper	79.5±0.5mm (width), 0.06~0.08mm (thickness), 80mm (roll diameter)
Interface	Serial+USB+Ethernet
Command	ESC/POS command
Character Size	ANK Font, Font A: 1.5×3.0mm (12×24dots), Font B: 1.1×2.1mm (9×17dots), Chinese Font
Data Buffer	128k bytes
Barcode Type	UPC-A /UPC-E /EAN13 /EAN8 /CODE39 /ITF /CODEBAR /CODE93 /CODE128 / QR Code
Operating Temperature	0°C to 45°C (operating); -10°C to 60°C (storage)
Print Head Life	100km
Cutter Life	1.5 million cuts
Weight	1.5kg

## Electrical

Power Input	DC 24V/2.5A
Power Supply Input	AC 110V/220V, 50-60Hz
Cash Drawer Input	DC 24V/1A

[Notice] : Specification are subject to change without notice