


Technical Specifications

APC Back-UPS 700VA, 230V, AVR, Universal and IEC Sockets | BX700U-MS | Downloaded on 03/26/2019 (EST)



APC Back-UPS 700VA, 230V, AVR, Universal and IEC Sockets

BX700U-MS

Call for More Information 1-800-880-877

- Battery Backup & Surge Protector for Electronics and Computers
- Includes: Qty 1 - Detachable 1.2 m IEC power cord, Qty 1 - Detachable 2.0 m NEMA 5-15P to IEC C13 power cord, User Manual

Output

| | |
|----------------------------------|-------------------------------------|
| Output power capacity | 390Watts / 700VA |
| Max Configurable Power (Watts) | 390Watts / 700VA |
| Nominal Output Voltage | 230V |
| Output Frequency (sync to mains) | 50/60 Hz +/-1 Hz |
| Output Frequency (not synced) | 50/60 Hz +/-1 Hz |
| Topology | Line Interactive |
| Waveform type | Stepped approximation to a sinewave |
| Output Connections | (1) IEC 320 C13 (Battery Backup) |
| Transfer Time | 4ms typical : 6ms maximum |

Input

| | |
|---|----------------------------------|
| Nominal Input Voltage | 230V |
| Input frequency | 50/60 Hz +/- 3 Hz (auto sensing) |
| Input Connections | IEC-320 C14, NEMA 5-15P |
| Cord Length | 1.22meters |
| Input voltage range for main operations | 140 - 300V |
| Number of Power Cords | 2 |
| Type of Input Protection Required | 3-pole breaker |


Batteries & Runtime

| | |
|-----------------------|--|
| Battery type | Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof |
| Typical recharge time | 6hour(s) |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Technical Specifications

APC Back-UPS 700VA, 230V, AVR, Universal and IEC Sockets | BX700U-MS | Downloaded on 03/26/2019 (EST)

| Batteries & Runtime | |
|-------------------------------|--|
| Replacement Battery | APCRBC110  |
| Expected Battery Life (years) | 2 - 5 |
| Runtime | View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site) |
| Efficiency | View Efficiency Graph (Available in Technical Tab on site) |

| Communications & Management | |
|-----------------------------|--|
| Interface Port(s) | USB |
| Control panel | LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : and Overload Indicators |
| Audible Alarm | Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm |

| Surge Protection and Filtering | |
|--------------------------------|----------------------------|
| Surge energy rating | 273Joules |
| Data Line Protection | RJ-11 Modem/Fax protection |

| Physical | |
|----------------------|---------------|
| Maximum Height | 200mm, 20.0CM |
| Maximum Width | 115mm, 11.5CM |
| Maximum Depth | 256mm, 25.6CM |
| Net Weight | 6.0KG |
| Shipping weight | 6.8KG |
| Shipping Height | 275mm, 27.5CM |
| Shipping Width | 295mm, 29.5CM |
| Shipping Depth | 340mm, 34.0CM |
| Color | Black |
| Master Carton Units | 2.0 |
| Master Carton Weight | 13.7 |

| Environmental | |
|-----------------------------|-----------|
| Operating Temperature | 0 - 40 °C |
| Operating Relative Humidity | 0 - 95 % |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Technical Specifications

APC Back-UPS 700VA, 230V, AVR, Universal and IEC Sockets | BX700U-MS | Downloaded on 03/26/2019 (EST)

| Environmental | |
|---|--------------|
| Operating Elevation | 0-3000meters |
| Storage Temperature | -15 - 40 °C |
| Storage Relative Humidity | 0 - 95 % |
| Storage Elevation | 0-9000meters |
| Audible noise at 1 meter from surface of unit | 45.0dBA |

| Conformance | |
|-------------------|---------------------------|
| Standard warranty | 2 years repair or replace |

| Sustainable Offer Status | |
|--------------------------|--------------------------|
| RoHS | Compliant |
| REACH | REACH: Contains No SVHCs |

  **ยินดีบริการ**  **ส่งทั่วไทย**   
ด้วยระบบขนส่งที่มั่นคงได้ **02-026-3361-2**  www.pospak.com  [facebook/pospak](https://facebook.com/pospak)  [@pospak](https://line.me/@pospak)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.