



APC Smart-UPS 3000VA LCD 230V

SMT3000I

Call for More Information +358 104466441


- Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
- Includes: CD with software, Documentation CD, Smart UPS signalling RS-232 cable, USB cable

| Output | |
|----------------------------------|--|
| Output power capacity | 2.7kWatts / 3.0kVA |
| Max Configurable Power (Watts) | 2.7kWatts / 3.0kVA |
| Nominal Output Voltage | 230V |
| Output Voltage Note | Configurable for 220 : 230 or 240 nominal output voltage |
| Output Voltage Distortion | Less than 5% at full load |
| Output Frequency (sync to mains) | 47 - 53 Hz for 50 Hz nominal, 57 - 63 Hz for 60 Hz nominal |
| Topology | Line Interactive |
| Waveform type | Sine wave |
| Output Connections | (8) IEC 320 C13 (Battery Backup) (2) IEC Jumpers (Battery Backup) (1) IEC 320 C19 (Battery Backup) |
| Transfer Time | 2ms typical |

| Input | |
|--|--|
| Nominal Input Voltage | 230V |
| Input frequency | 50/60 Hz +/- 3 Hz (auto sensing) |
| Input Connections | IEC-320 C20, Schuko CEE 7 / EU1-16P, British BS1363A |
| Input voltage range for main operations | 160 - 286V |
| Input voltage adjustable range for mains operation | 151 - 302V |
| Number of Power Cords | 1 |
| Other Input Voltages | 220, 240 |

Technical Specifications

APC Smart-UPS 3000VA LCD 230V | SMT3000I | Downloaded on 03/28/2019 (EST)

| Batteries & Runtime | |
|-------------------------------|--|
| Battery type | Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof |
| Typical recharge time | 3hour(s) |
| Replacement Battery | RBC55  |
| Expected Battery Life (years) | 3 - 5 |
| RBC Quantity | 1 |
| Extendable Run Time | 1 |
| Runtime | View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site) |
| Efficiency | View Efficiency Graph (Available in Technical Tab on site) |

| Communications & Management | |
|---|---|
| Interface Port(s) | SmartSlot, USB |
| Control panel | Multi-function LCD status and control console |
| Audible Alarm | Alarm when on battery : distinctive low battery alarm : configurable delays |
| Emergency Power Off (EPO) | Yes |
| Available SmartSlot™ Interface Quantity | 1 |

| Surge Protection and Filtering | |
|--------------------------------|---|
| Surge energy rating | 365Joules |
| Filtering | Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449 |

| Physical | |
|-----------------|---------------|
| Maximum Height | 435MM, 43.5CM |
| Maximum Width | 197MM, 19.7CM |
| Maximum Depth | 544MM, 54.4CM |
| Net Weight | 52.5KG |
| Shipping weight | 63.7KG |
| Shipping Height | 699MM, 69.9CM |
| Shipping Width | 381MM, 38.1CM |
| Shipping Depth | 762MM, 76.2CM |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Technical Specifications

APC Smart-UPS 3000VA LCD 230V | SMT3000I | Downloaded on 03/28/2019 (EST)

| Physical | |
|------------------|-------|
| Color | Black |
| Units per Pallet | 9.0 |

| Environmental | |
|---|---------------|
| Operating Temperature | 0 - 40 °C |
| Operating Relative Humidity | 0 - 95 % |
| Operating Elevation | 0-3000meters |
| Storage Temperature | -15 - 45 °C |
| Storage Relative Humidity | 0 - 95 % |
| Storage Elevation | 0-15000meters |
| Audible noise at 1 meter from surface of unit | 53.0dBA |
| Online thermal dissipation | 375.0BTU/hr |

| Conformance | |
|-------------------|---|
| Approvals | CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE |
| Standard warranty | 3 years repair or replace (excluding battery) and 2 year for battery, optional on-site warranties available, optional extended warranties available |

| Sustainable Offer Status | |
|--------------------------------|--------------------------------|
| RoHS | Compliant |
| REACH | REACH: Contains No SVHCs |
| PEP | Available in Documentation tab |
| EOLI | Available in Documentation tab |
| Other Environmental Compliance | China RoHS |

  **ยินดีบริการ**  **ส่งทั่วไทย** ด้วยระบบขนส่งที่มีประสิทธิภาพ   

 02-026-3361-2  www.pospak.com  [facebook/pospak](https://facebook.com/pospak)  @pospak

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.