



## Overview

Lead time	Usually Ships within 2 Weeks
-----------	------------------------------

## General

Provided equipment	Installation guide Rack mounting brackets
--------------------	--

## Physical

Number of rack unit	4U
Colour	Black
Depth	48.3 cm
Height	43.2 cm
Net weight	60.91 kg
Width	17.8 cm

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

## Batteries & Runtime

Number of battery blocks per string	10
Device mounting	Enclosed battery cartridge
Battery type	Lead-acid battery

Number of battery filled slots	0
Number of battery free slots	0
Number of battery replacement quantity	2
Battery voltage	120 V

### Packing Units

Package 1 Weight	65.45 kg
Package 1 Height	33 cm
Package 1 width	58.6 cm
Package 1 Length	63.3 cm
Number of Units in Package 3	6

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

### Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------