



### Overview

Lead time	Usually Ships within 2 Weeks
-----------	------------------------------

### General

Provided equipment	Installation guide Rack mounting brackets
--------------------	--

### Physical

Number of rack unit	2U
Colour	Black
Depth	66.7 cm
Height	8.5 cm
Net weight	56.36 kg
Width	43.2 cm

### Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

### Batteries & Runtime

Number of battery blocks per string	10
Device mounting	Enclosed battery cartridge
Battery type	Lead-acid battery

Number of battery filled slots	0
Number of battery free slots	0
Number of battery replacement quantity	2
Battery voltage	120 V

### Packing Units

Package 1 Weight	63.64 kg
Package 1 Height	24.3 cm
Package 1 width	59.6 cm
Package 1 Length	86.9 cm
Number of Units in Package 3	8

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

### Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------