



Overview

Model Name	APC Easy UPS SRV 1000VA 230V
Includes	CD with software , USB cable , User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Afghanistan , Albania , Algeria , Angola , Armenia , Austria , Belgium , Bolivia , Bosnia And Herzegovina , Botswana , Brunei Darussalam , Bulgaria , Burkina Faso , Cambodia , Cameroon , Central African Republic , Chad , Chile , Colombia , CONGO, THE DEMOCRATIC REPUBLIC OF THE , Croatia , Cyprus , Czech Republic , Denmark , Dominica , Egypt , Estonia , Finland , France , Gabon , Gambia , Georgia , Germany , Greece , Guadeloupe , Guinea , French Guiana , Hong Kong , Hungary , Iceland , Indonesia , Iraq , Ireland , Israel , Italy , Jordan , Kazakhstan , Latvia , Lebanon , Lesotho , Liberia , Liechtenstein , Lithuania , Luxembourg , Macedonia , Madagascar , Malawi , Malaysia , Malta , Martinique , Mauritania , Mauritius , Moldova , Republic Of , Mongolia , Morocco , Myanmar , Namibia , Netherlands , Netherlands Antilles , Niger , Nigeria , Norway , Oman , Pakistan , Papua New Guinea , Peru , Philippines , Poland , Portugal , Romania , Russian Federation , SAINT LUCIA , Senegal , Sierra Leone , Singapore , Slovakia (Slovak Republic) , Slovenia , South Africa , Spain , Sweden , Switzerland , Tajikistan , Thailand , Togo , Tunisia , Turkey , Turkmenistan , Ukraine , Uzbekistan , Viet Nam , Western Sahara , Zambia , Zimbabwe

Output

Output Power Capacity	800 Watts / 1000 VA
Max Configurable Power (Watts)	800 Watts / 1000 VA
Nominal Output Voltage	230V
Output Voltage Distortion	3%
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Other Output Voltages	220, 240V
Other Output Voltages	Double Conversion Online
Waveform Type	Sine wave
Output Connections	(3) IEC 320 C13 (Battery Backup)

Input

Nominal Input Voltage	230V
Input Frequency	40 - 70 Hz
Input Connections	IEC-320 C14
Input voltage range for main operations	160 - 280 V
Other Input Voltages	220 , 240

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Included Battery Modules	1
Typical recharge time	4 hour(s)

Communications & Management

Interface Port(s)	USB
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	600 Joules
---------------------	------------

Physical

Maximum Height	223.0 mm
Maximum Width	145.0 mm
Maximum Depth	288.0 mm
Net Weight	9.31 kg
Shipping Weight	10.6 kg
Shipping Height	330.0 mm
Shipping Width	235.0 mm
Shipping Depth	365.0 mm

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 (non-condensing) %
Operating Elevation	0-3000 meters
Storage Temperature	-20 - 50 °C
Storage Relative Humidity	0 - 95 (non-condensing) %
Storage Elevation	0-14763.6 meters
Audible noise at 1 meter from surface of unit	50.000 dB
Online Thermal Dissipation	372.000 BTU/hr

Conformance

Approvals	CE , IEC 62040-1-1 , IEC 62040-1-2
Standard warranty	2 year (manufacturer's defect)

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains SVHCs