



Uninterruptible Power Supply

# True Online Double Conversion UPS

# UPS

## HT11 series

### High Frequency Online UPS



1-3KVA 1Phase:1Phase

### Application

### Features

- True online double-conversion technology
- Wide input voltage range and stable power supply extends battery lifetime
- DSP technology
- Advanced PFC technology, input PF>99%
- Cold start
- Automatic battery charging on/off mode
- Lighting and surge protection
- LCD/LED display
- Smart RS232 port with monitoring software
- Smart slot for mission critical applications
- Power Factor 0.9

### Rear Panel



1KVA/900W

2KVA/1800W

3KVA/2700W

- 1 AC Input
- 2 Circuit Breaker
- 3 DC Input
- 4 Outlet
- 5 Modem/Tel/FAX
- 6 RS232/USB
- 7 SNMP

1k

2/3K



ยินดีบริการ 02-026-3361-2

ส่งทั่วประเทศ www.pospak.com

KERRY EXPRESS SCS EXPRESS J&T EXPRESS facebook/pospak @pospak



โทร. 1291-2553(หมู่1)  
โทร. 1291-2553(หมู่2)  
โทร. 1291-2553(หมู่3)

### Specification:

Model	HT1101S	HT1101L	HT1102S	HT1102L	HT1103S	HT1103L
Capacity	1kVA/900W		2kVA/1800W		3kVA/2700W	
<b>Input</b>						
Voltage	220/230/240Vac					
Voltage Range	220Vac ±25%					
Frequency	50/60Hz ±10%					
<b>Output</b>						
Voltage	220VAC ±5%					
Frequency	50/60Hz ±1%					
Harmonic Distortion	≤3% (linear load); ≤5% (non-linear load)					
Waveform	Pure Sine Wave					
Power Factor	0.9					
Crest Factor	3:1					
<b>Efficiency</b>						
AC to AC	>85%					
Battery Mode	>83%					
<b>Battery</b>						
Battery Voltage	36Vdc		72Vdc		96Vdc	
Battery Number	12V9.6AH*3pcs	External	12V9.6AH*6pcs	External	12V9.6AH*8pcs	External
Backup Time (Full Load)	5 Mins	Depend On Load	5 Mins	Depend On Load	5 Mins	Depend On Load
<b>Communication</b>						
Interface	RS232 / SNMP card(Optional) / USB(Optional)					
<b>Environment</b>						
Operation Temperature	0~40°C					
Humidity	0~95% (non-condensing)					
Audible Noise	≤45dB	≤50dB				
<b>Physics</b>						
Dimensions(W*D*H)mm	144*350*236		190*425*336		190*425*33	
Weight (KG)	12	6	22	10	26	10