

RD200

USB RFID
Desktop Reader

■ Feature

- USB keyboard emulation, plug and play or serial port emulation (RS232).
- Built-in antenna, two colors led visual indication and buzzer alert.
- Auto-detect card and UID or block data.
- Provide API development tool.
- Update firmware through usb interface without disassembling case.
- Support decimal and hexadecimal ID formats.
- Unique serial number for identification.
- Built-in user data storage space.
- Development Tools: Support BCB6,VB6,VB.NET sample program and VC,VB,BCB, DevC,C# library.
- Able to write [URL](#) to memory and users can simply open a webpage with the [NFC-enabled](#) mobile phone ([Utralight NTAG203](#)).



• PC Authentication



• Print control



• Program Development




• ID Identification



• Access Control



• Password Login



Tag Supported :
EM / TEMIC / HiTag S / ISO-14443A



125 KHz



13.56 MHz



134.2 KHz

■ Specification

Specs / Item	RD200-LF	RD200-M1
Transmit Frequency	125KHz / 134.2KHz	13.56MHz
Card Compatibility	EM4100 compatible class / SYRIS/FDX-B (ISO11784)	ISO-14443A (Mifare 1K S50 / 4K S70 4/7-byte UID / Mifare Ultralight / NTAG203)
Read Range	0 ~ 6 cm	0 ~ 5 cm
Communication	Compatible with versions 2.0, mini USB 5-pin connector	
Antenna	Built-in	
LED Indicator	Two-color LED visual indication	
Beep Tone	Built-in Buzzer	
Input Voltage	USB power, 5V / 200mA	
Operating Temperature	-20°C ~ +65°C, 5 ~ 95% RH	
Storage Temperature	-30°C ~ +85°C, 5 ~ 95% RH	
Dimensions	105 x 72 x 16 mm (W x H x D)	

❖ This specification is preliminary and subject to change without prior notice.



- Reader with magnetic back housing which can be held on metal materials (OA partition, PC outer case...etc.)

► Ordering Information

Item	Type
■ RD200-LF	USB RFID Desktop Reader- EM
■ RD200-M1	USB RFID Desktop Reader- Mifare

SYRIS ACCESS Reader
SYRIS Security System