

เอกสารข้อมูลผลิตภัณฑ์

ข้อมูลจำเพาะ



APC Easy UPS On-Line SRV 6000VA RM 230V with Extended Runtime Battery Pack

SRV6KRIL

Overview

Presentation High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.

Lead time Usually in Stock

Main

Main Input Voltage 230 V

Other Input Voltage 220 V
240 V

Main Output Voltage 230 V

Other Output Voltage 220 V
240 V

Rated power in W 6000 W

Rated power in VA 6000 VA

Output connector type Hard wire 3-wire (H N + E) 1

Number of rack unit 5U

Provided equipment Basic UPS signalling RS-232 cable
CD with software
Rack mounting brackets
User manual
USB cable

General

Number of power module filled slots 0

Number of power module free slots 0

Redundant No

Physical

Colour Black

Height 21.95 cm

Width 43.8 cm

Depth 61.5 cm

Net weight 78 kg

Mounting location Front

Mounting preference	Lower
Mounting mode	Rack-mounted with kit
USB compatible	Yes
Mounting position	Horizontal

Input

Input voltage limits	110...300 V half load 176...300 V full load
Number of input connectors	1 hard wire 3-wire (1P + N + E)
Network frequency	40...70 Hz auto sensing

Output

Maximum configurable power in VA	6000 VA
Maximum configurable power in W	6000 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Harmonic distortion	1 %
UPS type	Double conversion online
Wave type	Sine wave
Efficiency	94 % (full load)
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1

Conformance

Product certifications	CE EAC TISI
Standards	EN/IEC 62040-1 EN/IEC 62040-2

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-15...60 °C
Storage Relative Humidity	Non-condensing 0...95 %
Storage altitude	0...15000 m
Acoustic level	55 dB
Heat dissipation	1172 Btu/h
IP degree of protection	IP20

Batteries & Runtime

Battery type	Lead-acid battery
Battery voltage	240 V

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	9 h
Battery life	3...5 year(s)
Battery charger power	1170 W rated
Battery option	SRV240RLBP-9A 1 3024 VAh SRV240RLBP-9A 2 4536 VAh SRV240RLBP-9A 3 6048 VAh SRV240RLBP-9A 4 7560 VAh SRV240RLBP-9A

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Control panel	Multifunction LCD status and control console
Emergency power off	Yes
Free slots	1

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Packing Units

Package 1 Weight	88 kg
Package 1 Height	49 cm
Package 1 width	60 cm
Package 1 Length	87 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------