

# เอกสารข้อมูลผลิตภัณฑ์

ข้อมูลจำเพาะ



APC Smart-UPS On-Line, 3kVA,  
Tower, 230V, 8x C13+2x C19  
IEC outlets, SmartSlot, Extended  
runtime, W/O rail kit

SRT3000XLI

## Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

## Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	2700 W
Rated power in VA	3000 VA
Input Connection Type	BS1363A British IEC 60320 C20 Schuko CEE 7 / EU1-16P
Nb of power socket outlets	8 IEC 60320 C13 2 IEC Jumpers 2 IEC 60320 C19
Cable length	2.44 m
Number of cables	3
Battery type	Lead-acid battery
Provided equipment	CD with software Country-specific detachable power cord Documentation CD Installation guide Removable support feet USB cable Warranty card

## General

Product web sub-family	High density
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

## Physical

Colour	Black
Height	43.2 cm
Width	8.5 cm
Depth	63.5 cm
Net weight	31.3 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
Mounting position	Vertical

## Input

Network frequency	40...70 Hz auto-sensing
Input voltage limits	100...275 V adjustable (half load)

## Output

Maximum configurable power in W	2700 W
Harmonic distortion	Less than 2 %
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Crest factor	3 : 1
UPS type	Double conversion online
Wave type	Sine wave
Bypass type	Internal bypass (automatic and manual)
Maximum configurable power in VA	3000 VA

## Conformance

Product certifications	CE EAC RCM VDE
Marking	CE Mark
Standards	EN/IEC 62040-1 EN/IEC 62040-2

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0.00...15240.00 m

Acoustic level	55 dBA
Heat dissipation	703 Btu/h
IP degree of protection	IP20

## Batteries & Runtime

Battery recharge time	3 h
Number of battery replacement quantity	1
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Battery voltage	96 V
Battery charger power	168 W rated
Battery power in VAH	505 VAh runtime
Battery life	3...5 year(s)
Battery option	SRT96BP 1 1515 VAh SRT96BP 2 2525 VAh SRT96BP 3 3535 VAh SRT96BP 4 4545 VAh SRT96BP 5 5555 VAh SRT96BP 6 6565 VAh SRT96BP 8 8585 VAh SRT96BP 10 10605 VAh
Extended runtime	1

## Communications & Management

Free slots	1
Control panel	Multifunction LCD status and control console
Alarm	Audible and visible alarms prioritized by severity
Emergency power off	Yes

## Surge Protection and Filtering

Surge energy rate	340 J
-------------------	-------

## Packing Units

Package 1 Weight	36.74 kg
Package 1 Height	24.6 cm
Package 1 width	59.9 cm
Package 1 Length	87.1 cm
Number of Units in Package 3	6

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>

---

<b>WEEE</b>	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
<b>Optimized Energy Efficiency</b>	Energy efficient product
<b>Take-back</b>	Take-back program available

---

### **Contractual warranty**

---

<b>Warranty</b>	3 years repair or replace (excluding battery) and 2 years for battery
-----------------	---

---