

เอกสารข้อมูลผลิตภัณฑ์

ข้อมูลจำเพาะ



Rack ATS, 230V, 16A, (2) IEC 309 in, (1) IEC 309 out

AP4422



Overview

Lead time Usually in Stock

Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Plug standard	IEC 60309 16 A 2P + E
Number of rack unit	1U
Cable length	2.44 m
Number of cables	2
Provided equipment	Mounting hardware Rack mounting brackets Serial configuration cable

Physical

Colour	Black
Height	4.4 cm
Width	43.2 cm
Depth	23.6 cm
Net weight	4.21 kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Rack-mounted

Input

Network frequency	50/60 Hz
Max line current	16 A
Input current limits	16 A
Load capacity	3840 VA

Output

Max current draw	16 A
------------------	------

การละสิทธิ: เอกสารนี้ไม่มีวัตถุประสงค์เพื่อโฆษณา หรือใช้เพื่อกำหนดความเหมาะสม หรือความน่าเชื่อถือของผลิตภัณฑ์เห็นเหล่านี้สำหรับการใช้งานเฉพาะทาง

Number of power socket outlets	1 IEC 60309 16 A 2P + E
Power cable length	0.91 m

Conformance

Product certifications	CE EMC directive 2004/108/EC low voltage directive 2006/95/EC
Standards	EN/IEC 60950-1 UL 60950-1

Environmental

Ambient air temperature for operation	-5...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Package 1 Weight	5.95 kg
Package 1 Height	11.4 cm
Package 1 width	60 cm
Package 1 Length	34.9 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------