

เอกสารข้อมูลผลิตภัณฑ์

ข้อมูลจำเพาะ



Rack ATS, 230V, 32A, IEC 309 in, (16) C13 (2) C19 out



AP4424

Overview

Lead time Usually in Stock

Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Plug standard	IEC 60309 32 A 2P + E
Number of rack unit	2U
Cable length	2.44 m
Number of cables	2
Provided equipment	Rack mounting brackets RS-232 configuration cable Serial configuration cable

Physical

Colour	Black
Height	8.8 cm
Width	43.2 cm
Depth	23.6 cm
Net weight	6.94 kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Rack-mounted

Input

Network frequency	50/60 Hz
Max line current	32 A
Input current limits	32 A
Load capacity	7400 VA

Output

Max current draw	32 A
------------------	------

Number of power socket outlets	16 IEC 60320 C13 2 IEC 60320 C19
---------------------------------------	-------------------------------------

Protection type	Circuit breaker
------------------------	-----------------

Conformance

Standards	EN 55022 class A FCC part 15 class A
------------------	---

Environmental

Ambient air temperature for operation	-5...45 °C
--	------------

Relative humidity	5...95 %
--------------------------	----------

Operating altitude	0...10000 ft
---------------------------	--------------

Ambient air temperature for storage	-25...65 °C
--	-------------

Storage Relative Humidity	5...95 %
----------------------------------	----------

Storage altitude	0.00...15240.00 m
-------------------------	-------------------

Packing Units

Package 1 Weight	9.43 kg
-------------------------	---------

Package 1 Height	21 cm
-------------------------	-------

Package 1 width	58.4 cm
------------------------	---------

Package 1 Length	35.6 cm
-------------------------	---------

Offer Sustainability

Sustainable offer status	Green Premium product
---------------------------------	-----------------------

REACH Regulation	REACH Declaration
-------------------------	-----------------------------------

EU RoHS Directive	Compliant EU RoHS Declaration
--------------------------	--

Lead free	Yes
------------------	-----

Mercury free	Yes
---------------------	-----

RoHS exemption information	Yes
-----------------------------------	---------------------

Take-back	Take-back program available
------------------	-----------------------------

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------
