

Product datasheet

Specifications



Rack PDU, Basic, 1U, 16A, 208/230V, (12)C13



AP9565

Overview

Presentation	Reliable rack power distribution designed to increase manageability and efficiency in the data center. The output and input connections are (12)C13. Real-time remote monitoring of connected loads. User-defined alarms warn IT and data center managers of potential circuit overloads to prevent accidental power loss to critical equipment.
Lead time	Usually in Stock

Main

Main Input Voltage	200 V 208 V 230 V
Main Output Voltage	208 V 230 V
Input Connection Type	IEC 60320 C20
Number of rack unit	1U
Cable length	2.50 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets

Physical

Colour	Black
Height	4.4 cm
Width	44.7 cm
Depth	5.7 cm
Net weight	2.05 kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Rack-mounted

Input

Input current limits	16 A
Load capacity	3680 VA
Network frequency	50/60 Hz

Output

Number of power socket outlets	12 IEC 60320 C13
--------------------------------	------------------

Conformance

Product certifications	cUL listed CE Queensland Australia UL listed VDE
Standards	UL 60950

Environmental

Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Package 1 Weight	3.64 kg
Package 1 Height	7 cm
Package 1 width	46.4 cm
Package 1 Length	22.9 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------