

sewoo

3-Inch POS Printer

# SLK-TS100



- High Performance Easy Maintenance
- Easy maintenance with Jam release lever
- Easy maintenance for paper jam
- High speed printing at 8.6ips (220mm/sec)
- Ergonomic Design Entry-level Printer
- Simple and easy replacement of components including head, motor, cutter, PCB, etc
- Ideal for top exit printing with wall mount



Barcode



Durable



Paper Width



Easy Loading



Fast Speed



Compact Design



Easy Maintenance

## APPLICATION



## SPECIFICATIONS



### PRINTER CHARACTERISTICS

**Print Method**  
Direct thermal

**Print Speed**  
220mm/sec

**Print width**  
2.83"(72mm,  
adjustable by commands)

**Resolution**  
203 dpi

**Power**  
Power type : External SMPS  
AC : 110~220Vac 50/60Hz  
DC : 24Vdc / 2.5A

**Sensor**  
Paper end, Cover open

**Reliability**  
TPH life : 100km  
MCBF : 80,000H  
Cutter life : 1.5 Million cuts

**Drawer port**  
1circuit (24V,1A Max)



### PHYSICAL CHARACTERISTICS

**Dimension (W x D x H)**  
5.59" x 7.28" x 5.35"  
(142 x 185 x 136mm)

**Weight**  
2.25b(1.02Kg)



### INTERFACES

1. USB(B type)+  
Serial(RS-232C\_9pin)
2. USB(B type)+Serial  
(RS- 232C\_9pin)+  
Ethernet Built-in



### CERTIFICATIONS

CE, FCC, KC



### OPERATING CHARACTERISTICS

**Operating Temperature**  
32 ~ 113°F(0 ~ 45°C)

**Operating Humidity**  
10 ~ 80RH%

**Storage Temperature**  
14 ~ 140°F(-10 ~ 60°C)

**Storage Humidity**  
10 ~ 90RH%



### MEDIA CHARACTERISTICS

**Media Type**  
Thermal receipt paper

**Media Width**  
79.5±0.5mm

**Media Core Diameter**  
0.68 ~0.7"(17.5 ~ 18mm)

**Media Roll Diameter**  
3.1"(ø 80mm)

**Thickness**  
0.06~0.08mm



### SOFTWARE

**Emulations**  
ESC/POS Command compatible

**Drivers**  
Windows Driver  
(9X, 2000, 2003, XP, 7, 8, 10)

**SDK**  
Win, iOS, Android



### BARCODES

**1D**  
EAN-8, EAN-13, Code 39,  
Code 93, Code 128, ITF,  
UPC-A, UPC-E, Codabar

**2D**  
PDF 417, QR code



### FONTS / GRAPHICS

**Character Type**  
Font A(12x24), Font B(9x17),  
Chinese(Traditional/Simplified, 24x24),  
Korean(24x24), Japanese(24x24)

**Characters per line (CPL)**  
Font A(12x24) : 48cpl or 42cpl,  
Font B(9x17) : 64cpl,  
Chinese/Korean/Japanese: 24cpl

**Character set**  
95 Alphanumeric,  
16 International,  
128 x 18 Graphic



### ACCESSORIES

**Standard**  
Melody box

# sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea  
T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

#### USA, Inc.

Torrance, CA 90502, USA  
T. +1-310-617-7401  
E. NA\_sales@miniprnter.com

#### México Office

Cuahtémoc, D.F. Mexico. CP 06500  
T. +52-1-55-3232-9543 M. +52-1-55-143893  
E. LA\_sales@miniprnter.com

#### China Office

Shang hai shi, Song jiang qu  
T. +86-177-1729-9100  
E. sales@miniprnter.com

