



APC Smart-UPS 750VA, Tower, LCD 230V with SmartConnect Port

SMT750IC

Call for More Information (0) 2 617 5555

- Includes: USB cable

Output	
Output power capacity	500 Watts / 750VA
Max Configurable Power (Watts)	500 Watts / 750VA
Nominal Output Voltage	230V
Output Voltage Distortion	Less than 5 %
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz Sync to mains
Other Output Voltages	220, 240
Topology	Line interactive
Waveform type	Sine wave
Output Connections	(6) IEC 320 C13 (2) IEC Jumpers
Transfer Time	6 ms typical : 10 ms maximum
Input	
Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 3 Hz Auto-sensing
Input Connections	IEC 320 C14
Cord Length	1.8meters
Input voltage range for main operations	151 - 302 Adjustable, 160 - 280V
Number of Power Cords	1
Other Input Voltages	220, 240

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Smart-UPS 750VA, Tower, LCD 230V with SmartConnect Port | SMT750IC | Downloaded on 03/12/2021 (EST)

Batteries & Runtime	
Battery type	Lead-acid battery
Typical recharge time	3hour(s)
Replacement Battery	RBC48 
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Battery Charge Power (Watts)	49 Watts
Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Communications & Management	
Interface Port(s)	SmartSlot, USB
Control panel	Multifunction LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency Power Off (EPO)	Optional
Available SmartSlot™ Interface Quantity	1

Surge Protection and Filtering	
Surge energy rating	540Joules
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical	
Maximum Height	161MM, 16.1CM
Maximum Width	138MM, 13.8CM
Maximum Depth	369MM, 36.9CM
Net Weight	11.8KG
Shipping weight	14.23KG
Shipping Height	301MM, 30.1CM
Shipping Width	278MM, 27.8CM
Shipping Depth	499MM, 49.9CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Smart-UPS 750VA, Tower, LCD 230V with SmartConnect Port | SMT750IC | Downloaded on 03/12/2021 (EST)

Physical	
Color	Black
Units per Pallet	24.0

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0 - 15240meters
Audible noise at 1 meter from surface of unit	40.0dBA
Online thermal dissipation	90.0BTU/hr

Conformance	
Approvals	CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE
Standard warranty	3 years repair or replace (excluding battery) and 2 years for battery

Sustainable Offer Status	
RoHS	Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.