

XP-C230H / C300H

Thermal Receipt Printer

Key features

- Support QR CODE Printing
- Support Chinese GB18030
- 100MB Ethernet interface connection
- Avoid order missing
- Support black mark orientation
- Support oertype function
- Support 2048KB input buffer
- Support wall mountable and truck cable



Windows 7



Windows 8



Windows 10



Linux



Specifications

Model	XP-C230H	XP-C300H
Printing method	Direct thermal	
Printing speed	230mm/s	300mm/s
Paper width	79.5 ± 0.5mm	
Paper diameter	80mm	
Paper thickness	0.06~0.08mm	
Column capacity	576 dots/line 512 dots/line	
Line space	3.75mm (changeable using commands)	
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots	
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128 QR CODE	
Code page	PC347 (Standard Europe)、Katakana、PC850 (Multilingual)、PC860 (Portuguese)、PC863 (Canadian-French)、PC865 (Nordic)、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2)、PC852 (Latin2)、PC858、IranII、Latvian、Arabic、PT151 (1251)	
NV FLASH	256K Bytes	
Input buffer	2048K Bytes	
Power supply	DC 24V ≍ 2.5A	
Cash drawer control	DC 24V ≍ 1A	
Interface	USB / Lan / USB+WiFi / USB+Bluetooth	USB+Serial+Lan
Auto cutter	Partial	
Reliability	Printing head life: 100 km Auto cutter life: 1 million cuts	
Working environment	Temperature (0~45°C), humidity(10~80%)	
Storage environment	Temperature (-10~60°C), humidity(10~90%)	
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 10/Linux/OPOS	
Command	Compatible with ESC/POS	
Gross weight	1.78 kg	
Dimension	198×148×138mm (D×W×H)	