



Newland AIDC
Scanning Made Simple



NLS-HR3000-BT

WIRELESS 2D BARCODE SCANNER

FEATURES

○ Outstanding Performance

Equipped with an outstanding CPU, this CPU-based scanner can effortlessly capture high-density, high volume and distorted barcodes printed on paper or displayed on screen.

○ Durable Construction

The scanner is built into an IP52-sealed and drop resistant (1.5m) housing without moving parts and fortifies itself.

○ Replaceable Battery

Replaceable battery ensures continuous functionality and minimizes downtime.

○ Reliable and Stable Wireless Communication

Adopting Bluetooth 5.0 which is strong anti-interference and stable to transmit the data.



CMOS



1D Barcode



2D Barcode



IP Sealing



Drop



USB



Bluetooth



2600mAh

NLS-HR3000-BT

Performance

Image Sensor	1280×800 (megapixel) CMOS
Illumination	White LED
Aiming	laser diode
Symbologies	2D: PDF417, QR Code, Micro QR, Data Matrix, Aztec, Maxi Code, Chinese Sensible Code, GM Code, Micro PDF417, Code One. ID: Code 11, Code 128, Code39, GSI-128 (UCC/ENA-128), AIM 128, ISBT 128, Codabar, Code 93, UPC-A, UPC-E, Coupon, GSI Composite, EAN-13, EAN-8, ISSN, ISBN, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, ITF-6, ITF-14, Standard 2 of 5, China Post 25, MSI-Plessey, Plessey, GSI Databar (RSS), Code 49, Code 16K. Postal: USPS Postnet, USPS Intelligent Mail, Royal Mail, USPS Planet, KIX Post, Australian Postal OCR: Passport OCR, Chinese ID Card, China Travel Permit OCR
Resolution*	≥3mil
Typical Depth of Field*	EAN-13: 40mm-535mm (13mil) Code 39: 50mm-230mm (5mil) PDF 417: 45mm-215mm (6.7mil) Data Matrix: 30mm-245mm (10mil)
Scan Angle**	Pitch: ±60°, Roll: 360°, Skew: ±65°
Field of View	Horizontal 48°, Vertical 30°
Min Symbol Contrast*	15%

Wireless

Communication Mode	Synchronous, asynchronous and batch mode
Radio Technology	Bluetooth 5.0
Communication Distance	100m (direct line of sight in open air)
Memory Capacity	16384 pieces
Battery	2600 mAh lithium-ion battery
Expected Charge Time	6 hours (with power adapter)
Expected Battery Life	15 hours of continuous operation (scan once per 6 seconds)

Physical

Interface	USB Type-A, USB-KBW, USB-CDC, HID-POS
Operating Voltage	5VDC±5%
Dimensions (L×W×H)	Scanner: 117.5×67.5×144mm Cradle: 140×90×144.5mm
Weight	Scanner: 210g Cradle: 340.5g
Notification	Beep, LED indicator, vibration

Environmental

Operating Temperature	-10°C to 50°C (14°F to 122°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Battery Charge Temperature	0°C to 45°C (32°F to 113°F)
Humidity	5%-95% (non-condensing)
ESD	±15 KV (air discharge); ±8 KV (direct discharge)
Drop	Scanner: 1.5m Cradle: 1.2m
Sealing	Scanner: IP52

Certificates

Certificates & Protection	FCC Part15 Class B, CE EMC Class B, RoHS
---------------------------	--

*Test conditions: T=23°C; Illumination=300lux using incandescent lamp; sample printed barcodes made by Newland.

**Test conditions: Scan Distance= (min. DOF + max. DOF)/2; T=23°C; Illumination=300lux using incandescent lamp;

2D: QR code (15mil) 10 Bytes.

Specifications are subject to change without notice.

Version: V1.1

Newland AIDC

Add: No.1 Rujiang West Rd.,
Mawei, Fuzhou, Fujian 350001, China
Tel: +86-591-83979500
Fax: +86-591-83979216
Email: info@newlandaidc.com
Web: www.newlandaidc.com

Asia Pacific

Add: 6 Raffles Quay #14-06
Singapore 048582
Email: info@newlandaidc.com

Europe & Middle East

Add: Rolweg 25, 4104 AV Culemborg,
The Netherlands
Tel: +31 (0) 345 87 00 33
Email: sales@newland-id.com
Tech Support: tech-support@newland-id.com

North America & Latin America

Add: 46559 Fremont Blvd.,
Fremont, CA 94538, USA
Tel: +1 510 490 3888
Fax: +1 510 490 3887
Email: info@newlandaidc.com