

Commercial Display


Product Model ND98CMA

Taking simplicity, safety and flexibility to new levels. MAXHUB Commercial Display makes every organization more effective and productive.




Professional 4K Display

4K Resolution
Anti-Glare , 25% Haze



Wireless Screen Sharing

Share your screen through MAXHUB
Share app or wireless dongle




External Control

Display Control through IP
or RS232 protocol




Device Management

Manage through cloud based
MAXHUB PIVOT



Built-in Speakers

2x 10W



Upgrade Your Display

OPS slot availability to transform your
display into a windows-based display



Conformal Coating

Commercial level design of
hardware



Energy Saving

ErP Certified
Energy Star 8.0 Certified

Display

| | |
|-------------------------------|----------------------|
| Screen Size (class) | 98" |
| Diagonal | 97.5" / 247.7cm |
| Panel Type | ADS |
| Haze | 25% (Anti-Glare) |
| Aspect Ratio | 16:9 |
| Native Resolution | 3840*2160 |
| Refresh Rate | 60Hz |
| Brightness (Typ.) | 500 nits |
| Backlight Type | Direct Lit |
| Contrast Ratio | 1200:1 |
| Viewing Angle (H x V) | 178° (H / V) |
| Response Time | 8ms |
| Life Time (Min.) | ≥50,000 hours |
| Operation Hours (Hours / Day) | 24/7 |
| Orientation | Portrait / Landscape |

Internal Player

| | |
|------------------|--------------|
| Processor | A55 x4 |
| Graphic | Mali-G52 x2 |
| Memory | 4G |
| Storage | 32G |
| Operating System | Android 11.0 |
| UI Resolution | 4K |

Connectivity

| | |
|------------------|---|
| Input | HDMI in 2.0 x3 USB Type-C x1 (PD 65W) USB Type-A 3.0 x1 (for external peripherals) USB Type-A 2.0 x1 (only for firmware upgrade) RJ45 in x1 |
| Output | HDMI out 2.0 x1 SPDIF x1 (Optional) RJ45 out x1 Audio out x1 (3.5mini jack) |
| External Control | RS232 x1 / IR Receiver |
| Wi-Fi | Removable Wi-Fi Module Wi-Fi 6 Support 2.4G&5G 802.11ac/b/g/n/a/ax |
| OPS Slot | Yes , 80pin |

Mechanical Specification

| | |
|-------------------------------|--|
| Bezel Width (L x R x T x B) | 26 / 26 / 26 / 26 mm 1.02 / 1.02 / 1.02 / 1.02 inch |
| Product Dimension (W x H x D) | 2212.9 × 1268.4 × 79.4 mm 87.12 x 49.94 x 3.13 inch |
| Package Dimension (W x H x D) | 2360 × 1425 x 280 mm 92.91 x 56.10 x 11.02 inch |
| Product Weight (Net) | 69.90 kg / 154.10 pounds |
| Package Weight (Gross) | 90.8 kg / 200.2 pounds |
| VESA Mount (mm) | 800×600 |

Environmental Conditions

| | |
|-----------------------|----------------|
| Operation Temperature | 0° C ~ 40° C |
| Operation Humidity | 10% ~ 90%RH |
| Storage Temperature | -20° C ~ 60° C |
| Storage Humidity | 10% ~ 90%RH |

Power

| | |
|-----------------------------|------------------|
| Power Supply | 100-240V~50/60Hz |
| Power Consumption (Typical) | 340W |
| Power Consumption (Max) | 515W |

Sound

| | |
|----------------------|---------|
| Speaker Power Output | 2 x 10W |
|----------------------|---------|

Certification

| | |
|-------------|-------------|
| Safety | IEC 62368-1 |
| EMC | Class B |
| ErP | Yes |
| Energy Star | Yes |

Features

| | |
|--------------------------|--------------|
| Built-In Media Player | Yes |
| Device Management System | MAXHUB PIVOT |
| Screen Share | MAXHUB Share |

Accessory

| | |
|-------------------------|---|
| Included in the package | Power Cord, Wi-Fi Module x1, HDMI Cable (2m 6.56feet) x1 , Remote Control x1, Wall Mount x1 |
|-------------------------|---|

Optional



OPS (OPS62A)



Mobile Stand (ST41B)



Mobile Stand (ST23C)

Warranty

| | |
|---------|--------|
| Display | 3 year |
|---------|--------|