



# IT 1538

GEN 8

15 INCH HIGH-RESOLUTION TOUCHSCREEN

A cutting-edge point-of-sale terminal designed for modern businesses seeking high performance and reliability.



**FEATURING A NEXTGENERATION**

Multi-core processor, high-resolution

**IDEA FOR MEDIUM TO LARGE-SCALE BUSINESSES**

The Gen 8 model delivers superior performance, scalability, and energy efficiency.

# Features

- ◆ Equipped with a next-generation multi-core processor for fast, efficient, and reliable operation during heavy workloads.
- ◆ Features an enhanced, responsive touchscreen with high visibility and multi-touch support for smoother user interaction.
- ◆ Built with SSD storage for quick data access, improved durability.
- ◆ Compatible with the latest Windows and Android operating systems, ensuring flexibility with modern POS applications.
- ◆ Uses energy-saving components to reduce operational costs while maintaining high performance.



# Specifications



|                                |  |
|--------------------------------|--|
| <b>Processor</b>               | Intel® 8 <sup>th</sup> Generation Core™ i5 Latest-generation multi-core processor (Intel or equivalent) for high-speed performance   |
| <b>Memory</b>                  | RAM 8GB DDR4 (Up to 16GB)  |
| <b>Storage</b>                 | SSD M.2 Sata 256 GB (up to 512gb SSD)  |
| <b>OS compatible</b>           | <b>Pre-installed :</b> Windows 10 / Windows 10 IOT / Windows 11 (version varies based on configuration)<br><b>OS Compatibility :</b> Supports modern updates and integrations  |
| <b>Connectivity</b>            | 2x USB 3.0<br>4x USB 2.0<br>1x Ethernet (RJ45)<br>3x Serial (RS232)<br>1x HDMI (optional for external display support)<br>1x MIC_IN<br>1x LINE_OUT   |
| <b>Power Input</b>             | <b>Power Supply :</b> 100-240V AC, 50/60Hz<br><b>Energy Efficiency :</b> Low-power components for reduced energy consumption   |
| <b>Overall Dimensions</b>      | <b>Dimensions :</b> 380mm (H) x 280mm (W) x 100mm (D)<br><b>Weight :</b> 5.5kg (may vary based on configuration)   |
| <b>Environmental Tolerance</b> | <b>Operating Temperature :</b> 0°C to 40°C<br><b>Storage Temperature :</b> -20°C to 60°C<br><b>Humidity :</b> 10% to 90% non-condensing  |
| <b>Security</b>                | <b>Trusted Platform Module (TPM) :</b> Optional for secure hardware-based encryption<br><b>Password Protection :</b> Supported for BIOS and OS-level security<br><b>Peripheral Security :</b> Integrated security features for POS peripherals |
| <b>Additional Features</b>     | Built-in speakers for audio prompts. Optional customer-facing display or second screen integration. Supports VESA wall or pole mounts.   |
| <b>Certifications</b>          | PCI DSS/RoHS/FCC/ISO9001/CE  |